

Panel version

TECHNICAL SPECIFICATIONS

System contains 4 panels with a control router. It is meant for installations inside existing and operational VSAT or TVRO domes.

For installation of our Panel Version there should be at least 10cm clearance between the dish and the dome cover, to keep the dish fully operational.

- 4 panels (four 5G modems and 16 omnidirectional antennas in total, see "Panel" spec page 7 for more info)
- Dual-LEO (e.g. Starlink Maritime) connectivity
- **Panel Mounting:** panels can be mounted either vertically or horizontally (but not flat) near the dome's base. Thus, they will not interfere with the satellite dish system
- **Mounting brackets:** will be provided to fit the diameter of the dome (spec on page 12)
- **Control Router:** mounted flat in the dome's base.
- **Power:** 160W peak load. DC 12V, 12A (3x4sqmm) or AC 100V..240V (3x1.5sqmm)
- **Operating temperature:** -40° to +75°C
- **Cabling required:** Ethernet to the ship's firewall: Cat6A or Cat7 S/FTP (shielded)

Remarks: 360° non-blocked horizontal line of sight recommended

The systems comes with all parts/cables required, except the ethernet cable connecting the dome to the ship's network.

Optional SIM extender is available so SIM cards can be conveniently changed below deck. It does not require any extra cables (uses the same ethernet cable as for the user data).

